

Technical data

Technical data, Citymaster 1250/1250 C basic vehicle	
Engine and Transmission	
Engine	<ul style="list-style-type: none"> Water-cooled 4-cylinder YANMAR diesel engine with 2,189 ccm Power output of 35.4 kW at 3,000 rpm, adjusted to 33.0 kW at 2,600 rpm Direct fuel injection 60 litre tank volume Engine is below the limit values complying with the European Exhaust Emission Standard 97/68 EU Stage IIIa
Approval	<ul style="list-style-type: none"> EU type approval, basic machine as tractor
Drive	<ul style="list-style-type: none"> Hydrostatic drive with hydraulic gear reduction and all-wheel drive Drive control with automatic load regulation in transport and work modes or specifying the engine speed (noise limitation) Differential lock (Option for 1250)
Device drives	<ul style="list-style-type: none"> 2-circuit high pressure hydraulics, 195 bar Circuit 1 can be regulated, 0–22 l/min Circuit 2 is constant, 46 l/min Additional equipment for multipurpose deployment of 1250C
Driving and Work Characteristics	
Speed	<ul style="list-style-type: none"> Driving speed, automotive 0–30 kph Work mode, hydrostatic 0–16 kph Reversing 0–12 kph
Chassis and steering	<ul style="list-style-type: none"> Tubular steel, hydraulic articulated, 4-wheel chassis Integrated and damped floating axle compensation for optimal curb climbing ability
Brakes	<ul style="list-style-type: none"> Multiple safety brake system with hydrostatic brake via drive Additional hydraulic service brake via foot pedal Mechanical parking brake
Tyres	<ul style="list-style-type: none"> 195 R 14C (standard), 215/65 R 15 (comfort tyres) 26.00 x 12.00 – 12 (grass tyres), special tyres on request
Driver's cab	<ul style="list-style-type: none"> Single seat comfort cab with air sprung seat, adjustable to the driver's weight Ergonomic arrangement of operating elements Adjustable steering column Hot water heater and optional air-con unit Framed doors with sliding windows Folding wing mirrors, adjustable from inside
Load Values	
Permissible total weight	2,600 kg
Permissible axle load	1,500 / 1,600 kg (front/rear)
Dimensions	
H/B/L	Basic machine: 1,999 mm (cab) x 1,193 mm (standard tyres) x 3,255 mm Sweeper: 1,999 mm (cab) x 1,193 mm (standard tyres) x 3,969 mm
Wheelbase	1,430 mm
Track width	984 mm

We reserve the right to make technical improvements to machines with regard to shape, colour and design without notice.
Illustrations could contain optional equipment.